

PCIe Riser Card x1 Left Slot Adapter 1U w/ Flexible Cable

PEX1RISERF / PEX4RISERF / PEX8RISERF

DE: Bedienungsanleitung - de.startech.com
 FR: Guide de l'utilisateur - fr.startech.com
 ES: Guía del usuario - es.startech.com
 IT: Guida per l'uso - it.startech.com
 NL: Gebruiksaanwijzing - nl.startech.com
 PT: Guia do usuário - pt.startech.com

Packaging Contents

- 1 x Riser Card
- 1 x Instruction Manual

System Requirements

- PCI Express enabled computer system with available x1/x4/x8 PCIe slot
- Server chassis designed for riser card applications

Installation


WARNING! PCI Express cards, like all computer equipment, can be severely damaged by static electricity. Be sure that you are properly grounded before opening your computer case or touching your PCI Express card. StarTech.com recommends that you wear an anti-static strap when installing any computer component. If an anti-static strap is unavailable, discharge yourself of any static electricity build-up by touching a large grounded metal surface (such as the computer case) for several seconds. Also be careful to handle the PCI Express card by its edges and not the gold connectors.

1. Make sure that your system is unpowered and unplugged and you are grounded.
2. Remove the cover of your system (refer to computer system documentation, if necessary) so that the PCI Express expansion slot openings on the motherboard are accessible.
3. Align the PCI Express connector on the riser card with an available PCI Express slot.
4. Gently insert the card into the empty slot, making sure it is seated firmly. Fasten the card to the riser card mounting bracket on the computer chassis (refer to computer system documentation, if necessary).
5. Install the desired PCI Express card into the PCIe slot on the riser card and fasten securely to the computer chassis (refer to computer system documentation, if necessary).
6. Replace and fasten the computer cover.

PEX1RISERF



PEX4RISERF



*actual product may vary from photos

PEX8RISERF



Specifications

	PEX1RISERF	PEX4RISERF	PEX8RISERF
Bus Interface	PCI Express (x1 slot connector)	PCI Express (x4 slot connector)	PCI Express (x8 slot connector)
Connectors	x1 PCI Express slot	x4 PCI Express slot	x8 PCI Express slot
Flex Cable Length	7cm		
Operating Temperature	0°C ~ 60°C (32°F ~ 140°F)		
Storage Temperature	0°C ~ 60°C (32°F ~ 140°F)		
Humidity	5% ~ 95% RH		
Dimensions (LxWxH)	179.0mm x 100.0mm x 15.0mm		
Weight	30g	35g	45g

FCC Compliance Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Use of Trademarks, Registered Trademarks, and other Protected Names and Symbols

This manual may make reference to trademarks, registered trademarks, and other protected names and/or symbols of third-party companies not related in any way to StarTech.com. Where they occur these references are for illustrative purposes only and do not represent an endorsement of a product or service by StarTech.com, or an endorsement of the product(s) to which this manual applies by the third-party company in question. Regardless of any direct acknowledgement elsewhere in the body of this document, StarTech.com hereby acknowledges that all trademarks, registered trademarks, service marks, and other protected names and/or symbols contained in this manual and related documents are the property of their respective holders.

Technical Support

StarTech.com's lifetime technical support is an integral part of our commitment to provide industry-leading solutions. If you ever need help with your product, visit www.startech.com/support and access our comprehensive selection of online tools, documentation, and downloads.

For the latest drivers/software, please visit www.startech.com/downloads

Warranty Information

This product is backed by a two year warranty.

In addition, StarTech.com warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. StarTech.com does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of StarTech.com Ltd. and StarTech.com USA LLP (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.