



NOTES:

- 1.OPEN/SHORT/INTERMITTENCE 100% TEST.
- 2.DIELECTRIC STRENGTH:300V AC 5mA/0.01S.
- 3.INSULATION RESISTANCE:300V DC/0.01S 10MΩ MIN.
- 4.CONDUCTIVE RESISTANCE:2Ω MAX.

PIN ASSIGNMENT

P1	_____	P2	_____
1	_____	1	_____
2	_____	2	_____
3	_____	3	_____
4	_____	4	_____
5	_____	5	_____

5	IN MOLD	PE	/	KG
4	OVER MOLD	PVC 45P BLACK	/	KG
3	CONN	MICRO USB B/M SOLDER CONTACT:PIN G/F SHELL:NI-PLATED	1	SET
2	CONN	MINI USB B/F SOLDER CONTACT:PIN G/F SHELL:NI-PLATED	1	SET
1	PCB	PCB T=0.80mm	A/R	M
No	PART NUMBER	MATERIAL DESCRIPTION	Q'TY	UNITS
8			5	

THIRD ANGLE PROJECTION

GENERAL NOTES
DIMENSIONS ARE IN MM - DO NOT SCALE

THIS DOCUMENT CONTAINS CONFIDENTIAL,
PROPRIETARY INFORMATION THAT IS
PROPERTY OF STARTECH.COM

PRODUCT ID	UUSBMUSBMF
DESCRIPTION	Micro USB to Mini USB 2.0 Adapter M/F
DO NOT SCALE	SHEET: 1 OF: 1
	UPLOAD DATE: 1/5/2021

8 7 6 5 4 3 2 1

F F

E E

D D

C C

B B

A A